RÔTISSERIE

FauxFlame TM FFS1425-6G

DESIGN

The FAUXFLAME range of rotisseries has been designed with performance, practicality and mobility in mind. Light weight and compact FAUXFLAME is the ideal rotisserie for markets and food trucks and offers rapid production together with excellent cooking quality.

Conscious of the costs involved for our clients, the FAUXFLAME rotisserie has energy-saving infrared burners, patented by Rotisol, that enable the rapid roasting of a variety of products.

FEATURES

- Independent motor for each spit
- □ Spits with Bakelite handles
- □ Independent infrared gas burners with interchangeable ceramic bricks
- 2 K-glass doors (removable for transport)
- □ Bottom drip tray with drainage tap
- Optional lighting

TECHNICAL DETAILS

Overview of some of the standard features.



Replaceable ceramic bricks for significant financial savings.



Robust hinges designed for heavy use, with integrated locking in open and closed positions.



FFS1425-6G-SS

Gas safety ! separation of the gas and electric chambers avoids any risks of explosion.

00000



Independant floating, swinging and adjustable motors to for easy placement and removal of spits.



Anti-scald K-glass reduces external thermal radiation (energy saving). Glass overlaps drip pan to keep splatters inside (anti-slip protection).



Removable inside side-panels doubles protection from grease seeping into motors and other sensitive parts

ACCESSORIES

A variety of accessories are available. See video of available accessories online.


CUI1425 Anti-cutting prongless V-spit.		BPOR1425 Porchetta spit.	1	BRC1425 Rectangular basket spit.	
BS1425 Spit for ham / turkey.	+ + +	BRRO1425 Roast-clamp spit.	*	BA1425 Lamb/suckling- pig spit.	×
BCR1425 Spatchcock chicken basket.	the second and a s	DEC Spit mover.	R	PID1425 Tray for unspit- ting.	



FauxFlame TM

FFS1425-6G

Front view




Side view

17 3/4

·0·

h






Intertek

Revised : September 2021

SPECIFICATIONS

Capacity	30/36 chickens, 24/30 open chickens		
Gas power	91000 BTU/h		
Power supply	208-240V~60Hz; 3 Amps		
Electrical power	0,53 kW		
Weight and size (HxDxW)	463 Lbs ; 71 1/2 x 23 7/8 x 56 1/8 inches		
Shipping weight and size	620 Lbs ; 76 7/8 x 30 x 57 1/8 inches		
Warranty	1 year parts and labor		

Rotisol France, Inc. 1450 W. 228th Street, Unit 10, TORRANCE, CA 90501 <u>info@rotisolusa.com</u> Ph :310 671 7254



Top view



DISTRIBUTOR / AGENT