

DISPLAY PRESENTATION 3 LEVEL
PANORAMIC VENTILATED HEATED CABINET
REF.: 6MCV3LST.PANO



Non contractual photo

SPECIFICATIONS

Weight: 264 lb

An open self-service cross-section unit with independent loading per floor at the back and the front.

Ventilated heater

Epoxy exterior body, KGLASS glass and stainless steel.

3 levels of horizontal presentation in safety glass. (D:23 3/8 x W:25)x3.

Available height between shelves: :11,26 in

Total presentation capacity :i.e. the capacity of 18/36 shelled poultry

Digital display and electronic temperature control. Showcase lighting by LEDs.

Extinguishment of the heating of the shelves independently by switch.

Loading of products by level at the rear using hatches (in transparent PMMA) and at the front using a KGLASS glass door.

Furniture equipped with adjustable feet. Flat securit glass headband ref: GLP6MCV.

Power suply: 1 Phase + ground (240V~60Hz) , wire length: 80 in.

Electrical power: 2,17 KW

OPTIONS: basket.

The "K.GLASS" is a layer product manufactured on line, at high temperature, at oven output, where there fines metal particles are spread by pyrolysis on float clear surface, forming in that way an integrated layer to the door surface part. This layer is made with precious metals which give to the glass door quality of very low emissions, then a high resistance to the thermal radiance.